

# SMART's Storage Solutions

XceedLite 1.8"

MEMORY • FLASH • STORAGE • DISPLAYS • EMBEDDED

## XceedLite 1.8" Storage Products

SMART Modular Technologies' industrial grade XceedLite 1.8" solid state drives (SSDs) bring the advantages of non-volatile memory to mobile and embedded computing applications. Available in PATA and SATA-II interfaces, the XceedLite SSDs provide low-power, high reliability, solid state storage in an ultrasonically welded 1.8" housing. Making them ideal for use in applications such as ruggedized notebooks and other embedded mobile applications.

Available in capacities ranging from 4GB to 64GB, the XceedLite 1.8" SSDs typically require less than 1W active power at all densities. Low power requirements make the XceedLite SSDs well suited for mobile applications, where power savings can result in longer battery life. In fixed applications, lower power dissipation can also reduce the need and cost of cooling.

Utilizing a 3Gb/s interface, the XceedLite 1.8" SATA-II SSD has sustained throughputs of up to 72MB/s read and 55MB/s write, making it well suited for use in embedded applications such as tablet PC, ruggedized mobile computing, and as the operating system boot drive in a wide range of embedded and industrial applications.

## Industrial Grade Storage

An industrial grade storage solution, the XceedLite SSDs support industrial temperature ranges (-40°C to 85°C) and leverages advanced on-board error detection, correction algorithms and static wear leveling to ensure years of reliable operation. By using only single-level cell (SLC) NAND flash technology, the industrial grade XceedLite SSDs offer higher performance and increased reliability over other technologies. The XceedLite SSDs come with a 3-year limited warranty.

The XceedLite 1.8" SSDs are part of SMART's growing storage products portfolio of industrial grade SSD solutions. With a wide range of densities, performance, power requirements and interfaces, SMART storage products meet the needs of the most demanding applications. Visit [www.smartm.com](http://www.smartm.com) for more storage products from SMART.

## XCEEDLITE Product Family At-A-Glance

	Capacity (GB)	Performance (Sustained)
<b>XceedLite 1.8" SATA-II SSDs</b>		
1.8" SATA-II	4, 8, 16, 32, 64	72MB/s Read 55MB/s Write
<b>XceedLite 1.8" PATA SSDs</b>		
1.8" PATA	4, 8, 16, 32	45MB/s Read 25MB/s Write

- Typically requires less than 1W active power at all densities
- Up to 72MB/s sustained read, 55MB/s write
- Available in industrial (-40°C to 85°C) operating temperature range
- Advanced flash management for enhanced reliability



	XceedLite 1.8" SATA (Preliminary)	XceedLite 1.8" PATA
<b>Performance</b>		
Sustained (MB/s)	Up to 72/55MB/s R/W	Up to 45/25MB/s R/W
<b>Capacity</b>		
Min	4GB	4GB
Max	64GB	32GB
<b>Reliability</b>		
MTBF	1,550,969 hrs <sup>1</sup>	> 2,500,000 hrs <sup>1</sup>
Data Reliability	1 in 10 <sup>14</sup> bits read	
Data Retention	10 years @ 25C	
Endurance	> 260 years @200 GBytes/day write cycles, unlimited reads <sup>2</sup>	
<b>Power</b>		
Input Voltage	5V +/- 5%	3.3V +/- 5%
Idle (Typ)	0.52W	0.03W
Operational (Typ)	0.945W (Read) 0.955W (Write)	0.264W (Read) 0.231W (Write)
<b>Environmental</b>		
Operating Temp	Commercial (0°C to 70°C), Industrial (-40°C to 85°C)	
Operating Shock <sup>3</sup>	50g half-sine, 11msec, 3 shocks along each axis, X, Y, Z, in each direction	
Vibration <sup>3</sup>	15g peak to peak	
Altitude <sup>3</sup> (ft)	80,000 (24,384m)	
Relative Humidity <sup>3</sup>	5% to 95% non-condensing, RH	
Conformal Coating	Not Available	
Storage Temp	-55°C to 95°C	-65°C to 150°C
<b>Physical</b>		
Form Factor	1.8"	
Length (mm)	78.5	71
Width (mm)	54	54
Height (mm)	5	2.74
Connector	3Gb/s SATA-II	44-pin PATA

1 Based on the RDF2000 UTE C80-810 Telecom Standard at 25°C

2 Based on 64GB Drive

3 Based on MIL-STD-810F

Part Number	Capacity (GB)	Interface
<b>XceedLite - 1.8" SATA-II SSD</b>		
SG9STL1B4GAy01	4	3Gb/s SATA-II
SG9STL1B8GBNy01	8	3Gb/s SATA-II
SG9STL1B16GBNy01	16	3Gb/s SATA-II
SG9STL1B32GBNy01	32	3Gb/s SATA-II
SG9STL1B64GBNy01	64	3Gb/s SATA-II
<b>XceedLite - 1.8" PATA SSD</b>		
SG9PAT1G4GSMEAy	4	PATA
SG9PAT1G8GSMEBy	8	PATA
SG9PAT1G16GSMEBy	16	PATA
SG9PAT1G32GSMEBy	32	PATA

y (temperature)

y = null (0°C to 70°C, Commercial),

y = I (-40°C to 85°C, Industrial)

## Corporate Headquarters

Tel: (+1) 800-956-7627  
Tel: (+1) 510-623-1231  
Fax: (+1) 510-623-1434  
Email: info@smartm.com

## USA

Tel: (+1) 978-805-2100  
Fax: (+1) 978-805-2357  
Email: customers@smartm.com

## Latin America

Tel: (+55) 11 4417-7200  
Fax: (+55) 11 4417-7219  
Email: sac@smartm.com

## Europe

Phone: (+33) 1 43 54 58 80  
Fax: (+33) 1 43 26 64 81  
Email: euro.sales@smartm.com

## Asia/Pacific

Phone: (+65) 6232-2858  
Fax: (+65) 6232-2300  
Email: infoasia@smartm.com

[www.smartm.com](http://www.smartm.com)

